

KEW 2002A

KEW 2003A - Kyoritsu AC/DC Digital Clamp Meters

Rating: Not Rated Yet
2-3 Days

[Ask a question about this product](#)

Manufacturer[KYORITSU](#)

Description

- Equipped to measure both AC and DC current with transformer jaws of large diameter.
- Can measure AC and DC currents up to 2000A.
- Output terminal for connection to recorders.

AC A	400A/2000A (0 - 1000A) ±1.5%rdg±2dgt [50/60Hz] ±3%rdg±4dgt [40 - 500Hz] ±5%rdg±4dgt [500Hz - 1kHz] 2000A (1001 - 2000A) ±3%rdg±2dgt [50/60Hz]
DC A	400/2000A ±1.5%rdg±2dgt
AC V	400/750V ±1.5%rdg±2dgt [50/60Hz] ±1.5%rdg±4dgt [40Hz - 1kHz]
DC V	400/1000V ±1%rdg±2dgt
?	400/4000? ±1.5%rdg±2dgt
Continuity buzzer	buzzer sounds below 50±35?
Conductor size	Ø55mm max.
Frequency response	40Hz - 1kHz
Output	Recorder : DC400mV against AC/DC400A DC200mV against AC/DC2000A
Safety Standard	IEC 61010-1 CAT IV 600V , CAT III 1000V IEC 61010-031 IEC 61010-2-032
Power source	R6 (AA) (1.5V) × 2
Dimensions	250(L) × 105(W) × 49(D)mm
Weight	530g approx.
Included Accessories	7107A (Test leads)

Clampmeter: KEW 2002A

--

	9094 (Carrying Case)
	R6 (AA) × 2
	Instruction Manual
Optional Accessories	7256 (Output cord)