

KEW 2431

KEW 2431 - Kyoritsu Leakage Clamp Meters

Rating: Not Rated Yet
[Ask a question about this product](#)

Manufacturer[KYORITSU](#)

Description

- Frequency Selector Switch to eliminate the effect of harmonics.
- Three AC current ranges 20mA/200mA/200A.
- Rotary switch for easy one finger power-on and range selection.
- Resolution 0.01mA.

AC A (50/60Hz)	20/200mA/200A ±3%rdg±5dgt (20/200mA/100A) ±5%rdg±5dgt (200A)
AC A (WIDE)	20/200mA/200A ±2%rdg±4dgt [50/60Hz] (20/200mA/0 - 100A) ±5%rdg±6dgt [40 - 400Hz] (20/200mA/0 - 100A) ±5%rdg±4dgt [50/60Hz] (100.1 - 200A)
Conductor size	Ø24mm max.
Frequency response	40 - 400Hz
Effect of external stray magnetic field Ø15mm 100A	10mA AC max.
Safety Standard	IEC 61010-1 CAT III 300V IEC 61010-2-032
Power source	LR-44 (1.5V)× 2
Dimensions	149(L)× 60(W) × 26(D)mm
Weight	120g approx.
Included Accessories	9090 (Carrying Case) LR-44 × 2 Instruction Manual