

KEW 2432 - Leakage Clampmeter

KEW 2434 - Leakage Clampmeter

Rating: Not Rated Yet
[Ask a question about this product](#)

Manufacturer[KYORITSU](#)

Description

- Least affected by external stray magnetic field.
- 20mA AC max. in proximity to a 15mm-dia conductor carrying 100A AC
- Frequency Selector Switch to eliminate the effect of harmonics.
- Resolution 0.1mA.

AC A (50/60Hz)	400mA/4/100A $\pm 2\% \text{rdg} \pm 4 \text{dgt}$
AC A (WIDE)	400mA/4/100A $\pm 2\% \text{rdg} \pm 4 \text{dgt}$ [50/60Hz] $\pm 3\% \text{rdg} \pm 5 \text{dgt}$ [40 - 400Hz]
Conductor size	Ø28mm max.
Frequency response	40 - 400Hz
Effect of external stray magnetic field Ø15mm 100A	20mA AC max.
Safety Standard	IEC 61010-1 CAT III 300V IEC 61010-2-032
Power source	R03 (AAA) (1.5V) × 2
Dimensions	169(L) × 75(W) × 40(D)mm
Weight	220g approx.
Included Accessories	9097 Carrying Case R03 × 2 Instruction Manual