

KEW 2033 - AC/DC Clampmeter

AC/DC Digital Clamp Meter (40/300A)

Rating: Not Rated Yet
[Ask a question about this product](#)

Manufacturer[KYORITSU](#)

Description

- Smallest clamp meter capable of AC and DC current measurements.
- 300A auto ranging has minimum resolution of 0.01A AC/DC.
- Auto-zero function to allow one touch zero adjustment.

Specification:

AC A	40/300A $\pm 1\% \text{rdg} \pm 4 \text{dgt}$ [50/60Hz] (0 - 40A) $\pm 2.5\% \text{rdg} \pm 4 \text{dgt}$ [20Hz - 1kHz] (0 - 40A) $\pm 1.5\% \text{rdg} \pm 4 \text{dgt}$ [50/60Hz] (20 - 200A) $\pm 2.5\% \text{rdg} \pm 4 \text{dgt}$ [20Hz - 1kHz] (20 - 200A) $\pm 3.5\% \text{rdg}$ [50/60Hz] (200 - 300A) $\pm 4\% \text{rdg}$ [20Hz - 1kHz] (200 - 300A)
DC A	40/300A $\pm 1\% \text{rdg} \pm 4 \text{dgt}$ (0 - $\pm 40\text{A}$) $\pm 1.5\% \text{rdg} \pm 4 \text{dgt}$ (± 20 - $\pm 200\text{A}$) $\pm 3\% \text{rdg}$ (± 200 - $\pm 300\text{A}$)
Conductor size	Ø24mm max.
Frequency response	DC, 20Hz - 1kHz
Safety Standard	IEC 61010-1 CAT III 300V IEC 61010-2-032
Power source	LR-44 (1.5V) $\times 2$
Dimensions	147(L) $\times$ 59(W) $\times$ 25(D)mm
Weight	100g approx.
Included Accessories	9090 (Carrying Case) LR-44 $\times 2$ Instruction Manual