

Fluke 753 Documenting Process Calibrator

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer [Fluke](#)

Description

Product overview: Fluke 753 Documenting Process Calibrator

Fluke 753 Documenting Process Calibrator helps you work smarter and faster

The Fluke 753 is a powerful multifunction documenting calibrator that lets you download procedures, lists, and instructions created with software, and upload data for printing, archiving, and analysis. You'll find it does the work of several tools, with simultaneous source and measurement capabilities for all common process parameters. It sources, simulates, and measures pressure, temperature, and electrical signals in one rugged, hand-held calibration tool. It also automates calibration procedures, captures data for documentation, and helps you meet rigorous standards like ISO 9000, FDA, EPA, and OSHA regulations.

The 753 includes a USB interface and a USB communication cable to enable two-way communication with DPCTrack 2 and other instrumentation management applications. To create a seamless/paperless calibration management system consider adding Fluke DPCTrack2 Calibration Management software for use with your Fluke 753 and 754 or even legacy Fluke 743 and 744 calibrators.

Other useful features:

- Measures and sources pressure using any of 50 Fluke 700Pxx Pressure Modules
- Allows you to create and run automated as-found/as-left procedures to satisfy quality programs or regulations, and record and document results
- Holds up to a full week of downloaded procedures and calibration results
- Offers many flexible features like autostep, custom units, user-entered values during test, one-point and two-point switch testing, square root DP flow testing, programmable measurement delay and more.
- Offers compatibility with DPCTrack2 and many other asset management software packages
- Bright white dual display for reading both sourced and measured parameters simultaneously
- Easy-to-use multi-lingual interface
- Gas gauge and rechargeable Li-Ion battery for 10 hour uninterrupted use

Key features

Fluke 753 Documenting Process Calibrator

- Full-featured documenting process calibrator for calibrating and troubleshooting
- Measures volts, mA, RTDs, thermocouples, frequency, and ohms to test sensors, transmitters and other instruments
- Sources and simulate volts, mA, pressure, thermocouples, RTDs, frequency, ohms, and pressure to calibrate transmitters
- Powers transmitters during test using loop supply with simultaneous mA measurement

Specifications: Fluke 753 Documenting Process Calibrator

Measurement Accuracy

Voltage DC	Range /Resolution	1 Year	2 Years
	100.000 mV	0.02% + 0.005 mV	0.03% + 0.005 mV
	3.00000 V	0.02% + 0.00005 V	0.03% + 0.00005 V
	30.0000 V	0.02% + 0.0005 V	0.03% + 0.0005 V
	300.00 V	0.05% + 0.05 V	0.07% + 0.05 V
Voltage AC	3.000 V (40 Hz to 500 Hz) / 0.001 V	0.5% + 0.002 V	1.0% + 0.004 V
	30.00 V (40 Hz to 500 Hz) / 0.01 V	0.5% + 0.02 V	1.0% + 0.04 V
	300.0 V (40 Hz to 500 Hz) / 0.1 V	0.5% + 0.2 V	1.0% + 0.2 V
Current DC	30.000 mA	0.01% + 5 uA	0.015% + 7 uA
	110.00 mA	0.01% + 20 uA	0.015% + 30 uA
Resistance	10.000 ?	0.05% + 50 m?	0.07% + 70 m?
	100.00 ?	0.05% + 50 m?	0.07% + 70 m?
	1.0000 k?	0.05% + 500 m?	0.07% + 0.5 ?
	10.000 k?	0.1% + 10 ?	0.15% + 15 ?
Frequency	1.00 to 110.00 Hz / 0.01 Hz		0.05 Hz
	110.1 to 1100.0 Hz / 0.1 Hz		0.5 Hz
	1.101 to 11.000 kHz / 0.001 kHz		0.005 kHz
	11.01 to 50.00 kHz / 0.01 kHz		0.05 kHz

Source Accuracy

		1 Year	2 Years
Voltage DC	100.000 mV	0.01% + 0.005 mV	0.015% + 0.005 mV
	1.00000 V	0.01% + 0.00005 V	0.015% + 0.0005 V
	15.0000 V	0.01% + 0.0005 V	0.015% + 0.0005 V
Current DC	22.000 mA (source)	0.01% + 0.003 mA	0.02% + 0.003 mA
	Current sink (simulate)	0.02% + 0.007 mA	0.04% + 0.007 mA
Resistance	10.000 ?	0.01% + 10 m?	0.015% + 15 m?
	100.00 ?	0.01% + 20 m?	0.015% + 30 m?
	1.0000 k?	0.02% + 0.2 ?	0.03% + 0.3 ?
	10.000 k?	0.02% + 3 ?	0.03% + 5 ?
Frequency	0.1 to 10.99 Hz		0.01 Hz
	0.01 to 10.99 Hz		0.01 Hz
	11.00 to 109.99 Hz		0.1 Hz
	110.0 to 1099.9 Hz		0.1 Hz
	1.100 to 21.999 kHz		0.002 kHz
	22.000 to 50.000 kHz		0.005 kHz

Technical Data

Data log functions	Measure functions	Voltage, current, resistance, frequency, temperature, pressure
	Reading rate	1, 2, 5, 10, 20, 30, or 60 readings/minute
	Maximum record length	8000 readings (7980 for 30 or 60 readings/minute)
Ramp functions	Source functions	Voltage, current, resistance, frequency, temperature
	Rate	4 steps/second
	Trip detect	Continuity or voltage (continuity detection not available when sourcing current)
Loop power function	Voltage	Selectable, 26 V
	Accuracy	10%, 18 V minimum at 22 mA
	Maximum current	25 mA, short circuit protected
	Maximum input voltage	50 V DC
Step functions	Source functions	Voltage, current, resistance, frequency, temperature
	Manual step	Selectable step, change with arrow buttons
	Autostep	Fully programmable for function, start delay, stepvalue, time per step, repeat

Environmental Specifications

Operating temperature	-10°C to +50°C
Storage temperature	-20°C to +60°C
Dust/water resistance	Meets IP52, IEC 529
Operating altitude	3000 m above mean sea level (9842 ft)

Fluke 753 Documenting Process Calibrator

Safety Specifications

Agency approvals CAN/CSA C22.2 No 1010.1-92, ASNI/ISA S82.01-1994, UL3111, and EN610-1:1993

Mechanical and General Specifications

Size 136 x 245 x 63 mm (5.4 x 9.6 x 2.5 in)

Weight 1.2 kg (2.7 lb)

Batteries Internal Battery Pack Li-ion: 7.2 V, 4400 mAh, 30 Wh

Battery life > 8 hours typical

Battery replacement Via snap-shut door without opening calibrator; no tools required

Side port connections Pressure module connector

USB Connector to interface to your PC

Connection for optional battery charger/eliminator

Data storage capacity 1 week of calibration procedures results

90 day specifications The standard specification interval for the 750 Series are 1 and 2 years.

Typical 90 day measurement and source accuracy can be estimated by dividing the one year "% of reading" or "% of output" specifications by 2.

Floor specifications, expressed as "% of full scale" or "counts" or "ohms" remain constant.

Temperature, Resistance Temperature Detectors

Degrees or % of reading - Type (?)	Range °C	Measure °C ¹	
		1 year	2 year
100 ? Pt (385)	-200 to 100	0.07°C	0.14°C
	100 to 800	0.02% + 0.05°C	0.04% + 0.10°C
200 ? Pt (385)	-200 to 100	0.07°C	0.14°C
	100 to 630	0.02% + 0.05°C	0.04% + 0.10°C
500 ? Pt (385)	-200 to 100	0.07°C	0.14°C
	100 to 630	0.02% + 0.05°C	0.04% + 0.10°C
1000 ? Pt (385)	-200 to 100	0.07°C	0.14°C
	100 to 630	0.02% + 0.05°C	0.04% + 0.10°C
100 ? Pt (3916)	-200 to 100	0.07°C	0.14°C
	100 to 630	0.02% + 0.05°C	0.04% + 0.10°C
100 ? Pt (3926)	-200 to 100	0.08°C	0.16°C
	100 to 630	0.02% + 0.06°C	0.04% + 0.12°C
10 ? Cu (427)	-100 to 260	0.2°C	0.4°C
120 ? Ni (672)	-80 to 260	0.1°C	0.2°C
Source current	Source °C	Allowable current ²	
	1 year	2 year	
1 mA	0.05°C	0.10°C	0.1 mA to 10 mA
	0.0125% + 0.04°C	0.025% + 0.08°C	
500 ?A	0.06°C	0.12°C	0.1 mA to 1 mA
	0.017% + 0.05°C	0.034% + 0.10°C	
250 ?A	0.06°C	0.12°C	0.1 mA to 1 mA
	0.017% + 0.05°C	0.034% + 0.10°C	
150 ?A	0.06°C	0.12°C	0.1 mA to 1 mA
	0.017% + 0.05°C	0.034% + 0.10°C	
1 mA	0.05°C	0.10°C	0.1 mA to 10 mA
	0.0125% + 0.04°C	0.025% + 0.08°C	
1 mA	0.05°C	0.10°C	0.1 mA to 10 mA
	0.0125% + 0.04°C	0.025% + 0.08°C	
3 mA	0.2°C	0.4°C	0.1 mA to 10 mA
1 mA	0.04°C	0.08°C	0.1 mA to 10 mA

1. For two and three-wire RTD measurements, add 0.4°C to the specifications.

2. Supports pulsed transmitters and PLCs with pulse times as short as 1 ms

Temperature, Thermocouples

Type	Source °C	Measure °C		Source °C	
		1 year	2 years	1 year	2 years
E	-250 to -200	1.3	2.0	0.6	0.9
	-200 to -100	0.5	0.8	0.3	0.4
	-100 to 600	0.3	0.4	0.3	0.4
	600 to 1000	0.4	0.6	0.2	0.3
N	-200 to -100	1.0	1.5	0.6	0.9
	-100 to 900	0.5	0.8	0.5	0.8
	900 to 1300	0.6	0.9	0.3	0.4
J	-210 to -100	0.6	0.9	0.3	0.4
	-100 to 800	0.3	0.4	0.2	0.3
	800 to 1200	0.5	0.8	0.3	0.3
K	-200 to -100	0.7	1.0	0.4	0.6
	-100 to 400	0.3	0.4	0.3	0.4
	400 to 1200	0.5	0.8	0.3	0.4
	1200 to 1372	0.7	1.0	0.3	0.4

Fluke 753 Documenting Process Calibrator

T	-250 to -200	1.7	2.5	0.9	1.4
	-200 to 0	0.6	0.9	0.4	0.6
	0 to 400	0.3	0.4	0.3	0.4
B	600 to 800	1.3	2.0	1.0	1.5
	800 to 1000	1.0	1.5	0.8	1.2
	1000 to 1820	0.9	1.3	0.8	1.2
R	-20 to 0	2.3	2.8	1.2	1.8
	0 to 100	1.5	2.2	1.1	1.7
	100 to 1767	1.0	1.5	0.9	1.4
S	-20 to 0	2.3	2.8	1.2	1.8
	0 to 200	1.5	2.1	1.1	1.7
	200 to 1400	0.9	1.4	0.9	1.4
C	1400 to 1767	1.1	1.7	1.0	1.5
	0 to 800	0.6	0.9	0.6	0.9
	800 to 1200	0.8	1.2	0.7	1.0
L	1200 to 1800	1.1	1.6	0.9	1.4
	1800 to 2316	2.0	3.0	1.3	2.0
	-200 to -100	0.6	0.9	0.3	0.4
U	-100 to 800	0.3	0.4	0.2	0.3
	800 to 900	0.5	0.8	0.2	0.3
	-200 to 0	0.6	0.9	0.4	0.6
BP	0 to 600	0.3	0.4	0.3	0.4
	0 to 1000	1.0	1.5	0.4	0.6
	1000 to 2000	1.6	2.4	0.6	0.9
XK	2000 to 2500	2.0	3.0	0.8	1.2
	-200 to 300	0.2	0.3	0.2	0.5
	300 to 800	0.4	0.6	0.3	0.6