

Rental AC High Voltage Tester -

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer [HiPotronics/ Haefely](#)

Description

Overview

Hipotronics 100HVT-DI Digital AC Hipot Tester

- 100kV AC hipot, Digital Controller
- Adjustable and Programmable test parameters such as target voltage, maximum leakage, ramp rate, and dwell time
- Lightweight, rugged design, IP67-rated case with wheels and adjustable handle
- Universal Mains powered
- Meets ANSI/SIA A92.2 test specifications

Specification:

Model Number		30HVT-DI	60HVT-DI	120HVT-DI	100HVT-DI
System Output	Voltage	0 - 30 kV AC	0 - 60 kV AC	0 - 120kV AC	0-100KV AC
	Frequency	50/60 Hz			
	Current	10 mA			50mA (100kV Tap) 100mA (50kV Tap)
Current Meter		0 - 100 μA, 0 - 10 mA			0-1000uA / 0-100mA
Metering Accuracy		±1% of full scale			
Voltage Divider Location		Internal or External		External	
Dimensions (W x H x D)	Control	19.5 x 13.7 x 20 in (50 x 35 x 51 cm)			
	Bonnet	17 x 13 x 13 in (36 x 30 x 33 cm)	17 x 14 x 15 in (43 x 36 x 38 cm)	16 x 24 x 14 in (41 x 61 x 33 cm)	
Weight	Control	35lbs (16kg)			38lbs (17kg)

	Bonnet	30lbs (14kg)	68lbs (31kg)	135lbs (61kg)
Input Voltage & Frequency		120 V - 240 V, 50 Hz - 60 Hz		
Duty Cycle		5 min ON/5 min OFF repeated maximum of 6 times, then OFF for 2 hrs		

Contact Us for Quotation