

Rental MicroOhmmeter - DRM-100

Rating: Not Rated Yet

[Ask a question about this product](#)

Manufacturer [Adwel](#)

Description

Overview

- Precise contact resistance measurement
- True DC current is automatically ramped up and down
- Test cycle programmable from 10-60 seconds
- High input insulation level. Up to 1000 Volts on device under test
- Large, bright, high resolution, color screen
 - Continuous mode for trouble shooting
- High accuracy and resolution
- Emergency OFF button and auxiliary grounding terminal for safety
- High strength and waterproof Instrument case for rough field use
- Test leads and accessories in separate carrying case
- Also available with internal memory, printer, USB port. Model DRR-100
- Color screen
- Auto range

Specification

90 to 265 V 50/60 Hz.	Power
600 VA	Test
10 to 100 Amps	Current
10-60 seconds at	Test Period
10-100 Amps	Auto
Continuous at 20 Amps	ranges at
0.1 micro-ohms to	10-100
1999.9 micro-ohms	Amps
2000 micro-ohms to	Accuracy
19999 micro-ohms	Display
0.1 micro-ohms to	Resolution
199.99 milliohms (at 10	Graphic
Amps only)	User
± 0.5% of reading ±	Interface
0.5% of range	Insulation
4 1/2 digits	Level
12 x 9cm (4 3/4" x	Housing
3 1/2") bright LCD	Environme
display visible in bright	ntal
sunlight.	Weight
Display resolution of	Dimension
640 x 480.	s
1000 Vac on device	Approvals
under test	
Rugged, waterproof to	
IP-67	
Compliance: EN61010,	
EN61326	

Operating temperature: -10° to +50°C (+14° to +122°F)
Storage Temperature: -15° to +80°C (+5° to +176°F)
Relative Humidity: 0-95%, non-condensing
Instrument: 8.2 kg (18 lb.)
Std. Lead Kit: 11.3 kg (25 lb.)
Instrument: 47 x 35.7 x 17.6 cm (18 1/2" x 14" x 7")

Contact Us for Quotation !